




# DATASYM

POS Solutions for Tomorrow



## XR-650

### HEAVY DUTY PERFORMANCE FEATURES

- ❖ Top of the line Epson™ 301A Single Station Thermal Printer
- ❖ Dual Spring Activated Key Switches
- ❖ 98 Key Configurable Keyboard
- ❖ 5.7", 10 Line Color LCD Operator Display
- ❖ Standard Ethernet Communications, IRC, Two Configurable RS232 Ports, Two USB Ports

### SOFTWARE FEATURES

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>• Approximately 65,000 Items</li> <li>• Dedicated SKU Keys</li> <li>• SKUs Accessed through IRC</li> <li>• Split Pricing on Items</li> <li>• 10 Shift Levels</li> <li>• Mix &amp; Match</li> <li>• Items Inquiry &amp; Price Override</li> <li>• Item Age Verification</li> <li>• 20 Digit Items *</li> <li>• 20 Character Alpha Descriptors*</li> <li>• 150 Departments *</li> <li>• 999 Sub-Departments*</li> <li>• Sub-Department Links</li> <li>• 4 Tax Tables/Rates</li> <li>• 4 Foreign Currencies</li> <li>• 4 Paid Outs/Received on Account</li> <li>• Manager Receipt Control</li> <li>• Manager Control Flexibility</li> <li>• 9900 Management Functions *</li> <li>• 4 Data Capture Keys</li> <li>• 99 Key Data Entry*</li> <li>• 99 Macros*</li> <li>• 20 Media Types</li> <li>• Sales Suspend and Restore</li> </ul> | <ul style="list-style-type: none"> <li>• WIC Sales Items</li> <li>• WIC Shiftable Items</li> <li>• Manufacturers Coupon Scanning</li> <li>• 9 Percent Discounts &amp; Coupons</li> <li>• Global Discounts</li> <li>• 32,000 Pos./Neg. Check Files*</li> <li>• Debit(BuyPass)/EFT/EBT</li> <li>• Cash Declaration</li> <li>• Credit Card Authorization</li> <li>• 99 Clerks/Cashiers*/Managers</li> <li>• Floating Cashiers</li> <li>• Programmable "Automatic Cashier Logoff"</li> <li>• Save Z Data for Future Poll</li> <li>• Cashier Productivity Reports</li> <li>• Periodic Totals</li> <li>• Stack Reports</li> <li>• Flash Programming</li> <li>• Soft Keyboard Layouts</li> <li>• 20 Register* IRC</li> <li>• Training Mode</li> <li>• Drawer Timer (audible alert tone)</li> <li>• Electronic Journal</li> <li>• Electronic Mail</li> </ul> |
|--|--|

### PERIPHERALS

- |  |   |  |
|--|---|--|
| <ul style="list-style-type: none"> <li>• Scanners, Scales &amp; combinations</li> <li>• Magnetic Card Reader</li> <li>• Slip Printers</li> </ul> | <ul style="list-style-type: none"> <li>• 2nd Cash Drawer</li> <li>• Bar Code Label Printer</li> <li>• PIN Pad</li> <li>• Scanners (SYMFINITE™)</li> </ul> | <ul style="list-style-type: none"> <li>• Check Reader</li> <li>• Receipt Printer</li> <li>• Radio Frequency Look-Up</li> <li>• DATACAP Credit Authorization</li> </ul> |
|--|---|--|

(Continued, see over)

## **INTERGRATION**

- SYMFINITE for Window™, Database Management Ethernet communications.
- Lableworks™
- Wholesaler Interfaces Can Be Accommodated
- COMM 2000 for Windows™ with Ethernet Communications
- Event Pricing for Windows™

## **COMMUNICATIONS - COMM2000™ SOFTWARE**

- Ethernet Communication Local/Wide Area Networks Internet
- Receive Sales Information
- Uninterrupted Polling
- Polling while Register is Operating (or “on” or “off” position)
- Delayed Polling
- Electronic Journal Capturing & Viewing
- Send/Receive Programming
- Multiple Store/Register Communications
- Host Item Look-up (SYMFINITE™)

## **SUPPORT**

- Technical Documentation
- Field Service Engineers
- Regional Support Training
- Electronic Bulletin Board
- Field Training Certification
- E-mail Support

## **HARDWARE FEATURES**

- Reliable System Components:
  - Single Station Thermal Printer
  - Easy to Read 10 Line Color Operator Display
  - Pop-Up Alpha Numeric Customer Display, Standard
  - 98 Key- One Touch Raised Keyboard
- Front Display - 10 Line Color
- Rear Display – 2 Line/16 Character Alpha Numeric
- Paper Roll:
  - 88mm x 76 mm
- Dimensions:
  - ECR 418 mm W x 445 mm D x 219 mm H
  - Drawer 16 3/4” W x 17 1/2” D x 4 1/2” H
- Shipping Weight: ECR & Cash Drawer
  - 48 lbs. (21.82 kg)
- Power Requirements:
  - 120V AC+-10%, 50/60 Hz
- Power Consumption:
  - 47 Watts
- Operation Temperature:
  - 32F to 104F (0C to 40C)
- Humidity Range:
  - 10% to 90% RH